

867 Product Transfer and Resale Report

X12/V4010/867: 867 Product Transfer and Resale Report

Publication:

867 Product Transfer and Resale Report

Functional Group=PT

This Standard contains the format and establishes the data contents of the Product Transfer and Resale Report Transaction Set (867) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to: (1) report information about product that has been transferred from one location to another; (2) report sales of product from one or more locations to an end customer; or (3) report sales of a product from one or more locations to an end customer, and demand beyond actual sales (lost orders). Report may be issued by either buyer or seller.

Heading:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
010	ST	Transaction Set Header	M	1			Must use
020	BPT	Beginning Segment for Product Transfer and Resale	M	1			Must use
050	DTM	Date/Time Reference	O	10			Used
050	DTM	Date/Time Reference	O	10			Used
LOOP ID - N1					5		
080	N1	Name	O	1			Used
100	N3	Address Information	O	2			Used
110	N4	Geographic Location	O	1			Used
LOOP ID - N1					5		
080	N1	Name	O	1			Used
100	N3	Address Information	O	2			Used
110	N4	Geographic Location	O	1			Used

Detail:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
LOOP ID - PTD					>1		
010	PTD	Product Transfer and Resale Detail	M	1			Must use
LOOP ID - N1					5		
050	N1	Name	O	1			Used
070	N3	Address Information	O	2			Used
080	N4	Geographic Location	O	1			Used
LOOP ID - QTY					>1		
110	QTY	Quantity	O	1			Used
120	LIN	Item Identification	O	1			Used

Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
LOOP ID - CTT					1	N3/010L	
010	CTT	Transaction Totals	O	1		N3/010	Used
030	SE	Transaction Set Trailer	M	1			Must use

Notes:

- 3/010L The number of line items (CTT01) is the accumulation of the number of LIN segments. If used, hash total (CTT02) is the sum of the value of quantities (QTY02) for each QTY segment.
- 3/010 The number of line items (CTT01) is the accumulation of the number of LIN segments. If used, hash total (CTT02) is the sum of the value of quantities (QTY02) for each QTY segment.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code Description: Code uniquely identifying a Transaction Set All valid standard codes are used.	M	ID	3/3	Must use
ST02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BPT Beginning Segment for Product Transfer and Resale

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

To indicate the beginning of the Product Transfer and Resale Report Transaction Set and transmit identifying data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BPT01	353	Transaction Set Purpose Code Description: Code identifying purpose of transaction set	M	ID	2/2	Must use
		Code Name 00 Original				
BPT02	127	Reference Identification Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	O	AN	1/30	Used
BPT03	373	Date Description: Date expressed as CCYYMMDD	M	DT	8/8	Must use
BPT04	755	Report Type Code Description: Code indicating the title or contents of a document, report or supporting item	O	ID	2/2	Used
		Code Name 01 Product Transfer				
BPT02	127	Reference Identification Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	O	AN	1/30	Used
BPT03	373	Date Description: Date expressed as CCYYMMDD	M	DT	8/8	Must use
BPT04	755	Report Type Code Description: Code indicating the title or contents of a document, report or supporting item	O	ID	2/2	Used

Syntax Rules:

1. P0506 - If either BPT05 or BPT06 is present, then the other is required.

Semantics:

1. BPT02 identifies the transfer/resale number.
2. BPT03 identifies the transfer/resale date.
3. BPT08 identifies the transfer/resale time.
4. BPT09 is used when it is necessary to reference a Previous Report Number.

DTM Date/Time Reference

Pos: 050	Max: 10
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier Description: Code specifying type of date or time, or both date and time	M	ID	3/3	Must use
		Code Name 090 Report Start				
DTM02	373	Date Description: Date expressed as CCYYMMDD	X	DT	8/8	Used

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

DTM Date/Time Reference

Pos: 050	Max: 10
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier Description: Code specifying type of date or time, or both date and time	M	ID	3/3	Must use
		Code Name 091 Report End				
DTM02	373	Date Description: Date expressed as CCYYMMDD	X	DT	8/8	Used

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Loop N1

Pos: 080	Repeat: 5
Optional	
Loop: N1	Elements: N/A

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
080	N1	Name	O	1		Used
100	N3	Address Information	O	2		Used
110	N4	Geographic Location	O	1		Used

N1 Name

Pos: 080	Max: 1
Heading - Optional	
Loop: N1	Elements: 6

User Option (Usage): Used

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual	M	ID	2/3	Must use
		Code Name DS Distributor				
N102	93	Name Description: Free-form name	X	AN	1/60	Used
N103	66	Identification Code Qualifier Description: Code designating the system/method of code structure used for Identification Code (67)	X	ID	1/2	Used
		Code Name 92 Assigned by Buyer or Buyer's Agent				
N104	67	Identification Code Description: Code identifying a party or other code	X	AN	2/80	Used
N105	706	Entity Relationship Code Description: Code describing entity relationship All valid standard codes are used.	O	ID	2/2	Used
N106	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual All valid standard codes are used.	O	ID	2/3	Used

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N3 Address Information

Pos: 100	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information Description: Address information	M	AN	1/55	Must use
N302	166	Address Information Description: Address information	O	AN	1/55	Used

N4 Geographic Location

Pos: 110	Max: 1
Heading - Optional	
Loop: N1	Elements: 3

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name Description: Free-form text for city name	O	AN	2/30	Used
N402	156	State or Province Code Description: Code (Standard State/Province) as defined by appropriate government agency	O	ID	2/2	Used
N403	116	Postal Code Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O	ID	3/15	Used

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop N1

Pos: 080	Repeat: 5
Optional	
Loop: N1	Elements: N/A

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
080	N1	Name	O	1		Used
100	N3	Address Information	O	2		Used
110	N4	Geographic Location	O	1		Used

N1 Name

Pos: 080	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual Code Name WH Warehouse	M	ID	2/3	Must use
N102	93	Name Description: Free-form name	X	AN	1/60	Used
N103	66	Identification Code Qualifier Description: Code designating the system/method of code structure used for Identification Code (67) Code Name 92 Assigned by Buyer or Buyer's Agent	X	ID	1/2	Used
N104	67	Identification Code Description: Code identifying a party or other code	X	AN	2/80	Used

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N3 Address Information

Pos: 100	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information Description: Address information	M	AN	1/55	Must use
N302	166	Address Information Description: Address information	O	AN	1/55	Used

N4 Geographic Location

Pos: 110	Max: 1
Heading - Optional	
Loop: N1	Elements: 3

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name Description: Free-form text for city name	O	AN	2/30	Used
N402	156	State or Province Code Description: Code (Standard State/Province) as defined by appropriate government agency	O	ID	2/2	Used
N403	116	Postal Code Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O	ID	3/15	Used

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop PTD

Pos: 010	Repeat: >1
Mandatory	
Loop: PTD	Elements: N/A

To indicate the start of detail information relating to the transfer/resale of a product and provide identifying data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	PTD	Product Transfer and Resale Detail	M	1		Must use
050		Loop N1	O		5	Used
110		Loop QTY	O		>1	Used

PTD Product Transfer and Resale Detail

Pos: 010	Max: 1
Detail - Mandatory	
Loop: PTD	Elements: 1

User Option (Usage): Must use

To indicate the start of detail information relating to the transfer/resale of a product and provide identifying data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PTD01	521	Product Transfer Type Code Description: Code identifying the type of product transfer	M	ID	2/2	Must use
		Code Name SD Ship and Debit Sale				
<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PTD01	521	Product Transfer Type Code Description: Code identifying the type of product transfer	M	ID	2/2	Must use

Syntax Rules:

1. P0203 - If either PTD02 or PTD03 is present, then the other is required.
2. P0405 - If either PTD04 or PTD05 is present, then the other is required.

Loop N1

Pos: 050	Repeat: 5
Optional	
Loop: N1	Elements: N/A

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
050	N1	Name	O	1		Used
070	N3	Address Information	O	2		Used
080	N4	Geographic Location	O	1		Used

N1 Name

Pos: 050	Max: 1
Detail - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code Description: Code identifying an organizational entity, a physical location, property or an individual <u>Code Name</u> SN Store	M	ID	2/3	Must use
N102	93	Name Description: Free-form name	X	AN	1/60	Used
N103	66	Identification Code Qualifier Description: Code designating the system/method of code structure used for Identification Code (67) <u>Code Name</u> 92 Assigned by Buyer or Buyer's Agent	X	ID	1/2	Used
N104	67	Identification Code Description: Code identifying a party or other code	X	AN	2/80	Used

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N3 Address Information

Pos: 070	Max: 2
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information Description: Address information	M	AN	1/55	Must use
N302	166	Address Information Description: Address information	O	AN	1/55	Used

N4 Geographic Location

Pos: 080	Max: 1
Detail - Optional	
Loop: N1	Elements: 6

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name Description: Free-form text for city name	O	AN	2/30	Used
N402	156	State or Province Code Description: Code (Standard State/Province) as defined by appropriate government agency	O	ID	2/2	Used
N403	116	Postal Code Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O	ID	3/15	Used
N404	26	Country Code Description: Code identifying the country	O	ID	2/3	Used
N405	309	Location Qualifier Description: Code identifying type of location All valid standard codes are used.	X	ID	1/2	Used
N406	310	Location Identifier Description: Code which identifies a specific location	O	AN	1/30	Used

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop QTY

Pos: 110	Repeat: >1
Optional	
Loop: QTY	Elements: N/A

To specify quantity information

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
110	QTY	Quantity	O	1		Used
120	LIN	Item Identification	O	1		Used

QTY Quantity

Pos: 110 Max: 1
 Detail - Optional
 Loop: QTY Elements: 3

User Option (Usage): Used

To specify quantity information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
QTY01	673	Quantity Qualifier Description: Code specifying the type of quantity	M	ID	2/2	Must use
		<u>Code</u> <u>Name</u> 39 Shipped Quantity				
QTY02	380	Quantity Description: Numeric value of quantity	X	R	1/15	Used
QTY03	C001	Composite Unit of Measure Description: To identify a composite unit of measure(See Figures Appendix for examples of use)	O	Comp		Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	M	ID	2/2	Must use
		<u>Code</u> <u>Name</u> EA Each				
QTY02	380	Quantity Description: Numeric value of quantity	X	R	1/15	Used
QTY03	C001	Composite Unit of Measure Description: To identify a composite unit of measure(See Figures Appendix for examples of use)	O	Comp		Used
	355	Unit or Basis for Measurement Code Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	M	ID	2/2	Must use

Syntax Rules:

1. R0204 - At least one of QTY02 or QTY04 is required.
2. E0204 - Only one of QTY02 or QTY04 may be present.

Semantics:

1. QTY04 is used when the quantity is non-numeric.

LIN Item Identification

Pos: 120	Max: 1
Detail - Optional	
Loop: QTY	Elements: 4

User Option (Usage): Used

To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN02	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)	M	ID	2/2	Must use
		Code Name VP Vendor's (Seller's) Part Number				
LIN03	234	Product/Service ID Description: Identifying number for a product or service	M	AN	1/48	Must use
LIN04	235	Product/Service ID Qualifier Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID	2/2	Used
		Code Name PN Company Part Number				
LIN05	234	Product/Service ID Description: Identifying number for a product or service	X	AN	1/48	Used

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

Comments:

1. See the Data Dictionary for a complete list of IDs.
2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Loop CTT

Pos: 010	Repeat: 1
Optional	
Loop: CTT	Elements: N/A

To transmit a hash total for a specific element in the transaction set

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		Used

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: CTT	Elements: 2

User Option (Usage): Used

To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items Description: Total number of line items in the transaction set	M	NO	1/6	Must use
CTT02	347	Hash Total Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.	O	R	1/10	Used

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 030	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments Description: Total number of segments included in a transaction set including ST and SE segments	M	NO	1/10	Must use
SE02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Comments:

- SE is the last segment of each transaction set.

Table of Contents

Product Transfer and Resale Report	2
Transaction Set Header	3
Beginning Segment for Product Transfer and Resale	4
Date/Time Reference	5
Date/Time Reference	6
Loop N1	7
Name	8
Address Information	9
Geographic Location	10
Loop N1	11
Name	12
Address Information	13
Geographic Location	14
Loop PTD	15
Product Transfer and Resale Detail	16
Loop N1	17
Name	18
Address Information	19
Geographic Location	20
Loop QTY	21
Quantity	22
Item Identification	23
Loop CTT	24
Transaction Totals	25
Transaction Set Trailer	26