



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: HT1210ISOCTR

2U rack/console component power center w/ digital IR remote for all audio/video components - Isobar Audio/Video Power Center

Highlights

- 12 AC outlets arranged in three filter banks; 10-ft. power cord
- 4 sequenced, individually controllable AC outlets; IR remote control device included
- 5700-joule surge suppression rating
- 3-line HD-compatible gold coaxial surge protection
- 1-line tel/modem surge protection with built-in splitter; 1-line Ethernet surge protection
- \$150,000 [Ultimate Lifetime Insurance](#) (USA/Canada only); lifetime product warranty



Applications

- Large home/business theater installations, high-definition TVs, PVRs, satellite and A/V receivers, subwoofers, DVD/CD players and more

Package Includes

- HT1210ISOCTR Isobar Audio/Video Power Center
- One hand-held IR remote control device; one 6-ft. gold coaxial cable; one 6-ft. phone cable; one 6-ft network cable
- Color-coordinated outlet/plug labels
- Hardware for 2U rackmounting
- Instruction manual with warranty information

Features

- 5700-joule surge suppression rating with EMI/RFI line noise filtering helps components perform at their peak (sharper, crisper video; deeper, fuller audio; and longer component life spans)
- Exclusive Isolated Filter Banks eliminate interference between connected components
- 3 built-in filter banks: Analog, Digital, High Current
- Metal housing safely withstands the strongest surges
- 12 surge-protected NEMA 5-15R AC outlets safeguard all audio/video components
- 4 sequenced, individually IR-controllable AC outlets work with either included remote device or with user-supplied universal learning IR remote to facilitate orderly system startup and shutdown
- 3 sets of surge-protected, HD-compatible 2.2 GHz Type F gold coaxial connectors safeguard components on cable, satellite and antenna connections; one 6-ft. gold coaxial cable included
- 1-line tel/modem surge protection safeguards personal video recorders (PVRs) on a single dial-up connection. Built-in splitter (1 jack in/2 jacks out) allows simultaneous connection of two devices sharing a single line; one 6-ft. phone cable included
- 1-line Ethernet surge protection safeguards equipment on a 10/100 Base T network connection; one 6-ft network cable included
- 10-ft. power cord with right-angle NEMA 5-15P plug permits convenient placement anywhere within a home/business theater system
- 2 digital LED displays and 12 additional diagnostic LEDs alert user to input voltage levels, component load levels and 4 operational conditions (power, protection, grounding, selected outlets)
- 2U rackmount or console installation options; rackmount hardware and removable rubber console feet included
- Illuminated master switch provides one-touch power control over all components
- 15A circuit breaker protects against dangerous system overload

- Fail-safe thermal fusing acts like an additional circuit breaker, shutting down the unit and connected equipment in the event of a catastrophe

Specifications

OVERVIEW	
Intended Application	Audio/Video
SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output watts	1440
Output volt amp capacity (amps)	12
Overload protection	15A circuit breaker
Outlet quantity / type	12 NEMA 5-15R
INPUT	
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P
Input plug features	Right-angle plug
Input cord length (ft.)	10 ft.
Input cord length (m)	3
Input cord gauge, type	14 gauge, SJT
LEDS ALARMS & SWITCHES	
Alarms	Audible alarm
Switches	Illuminated on/off power switch
Diagnostic LEDs	Dual digital LED displays and 12 additional diagnostic LEDs alert user to input voltage levels, component load levels and 4 operational conditions (power, protection, grounding, selected outlets)
SURGE / NOISE SUPPRESSION	
AC suppression joule rating	5700 joules
AC suppression response time	NM = instantaneous CM = < 1 ns
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
Safe thermal fusing	Yes
UL1499 let through rating	330V - UL verified
EMI / RFI filtering	Yes
Isolated filter banks	3
DATALINE SURGE SUPPRESSION	

Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	Yes
Cable (Coax) Protection Details	3 line (support 2.2GHz bandwidths)
Network (Ethernet) Protection	Yes
PHYSICAL	
Shipping weight (lbs)	16
Shipping weight (kg)	7.3
Unit Dimensions (HWD/in)	3.5 x 17.5 x 12
Unit Dimensions (HWD/cm)	8.8 x 43.8 x 30.5
Shipping Dimensions (HWD/in)	7.5 x 21.5 x 15.0
Shipping Dimensions (HWD/cm)	19.1 x 54.6 x 38.1
Unit weight (lbs)	13.5
Unit weight (kg)	6.1
Material of construction	Metal
Mounting accessories included	2U rackmounting hardware
Receptacle Color	Black
AC line cord color	Black
Style	Rack/Console
Form factors supported	2U rackmount/console installation
SPECIAL FEATURES	
Appearance	Attractive black housing and receptacles with silver faceplate
Right-Angle Plug	Yes
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1283 (EMI Filter)	UL1283
cUL / CSA (Canada)	cUL
Approvals	RoHS, TUV tested to UL standards 1449 & 962A
WARRANTY	

Standard warranty period	Lifetime
Connected equipment insurance (USA, Canada, Puerto Rico)	\$150,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3500.