



Right-Angle Cat6 Gigabit Molded UTP Ethernet Cable (RJ45 Right-Angle M to RJ45 M), Blue, 3 ft. (0.91 m)

MODEL NUMBER: N204-003-BL-RA







Highlights

- Space saving design
- Right Angle connector to Straight
- Cat6 Gigabit rated

System Requirements

 Use with Cat6, Cat5e, Cat5, or VoIP networks

Package Includes

3-ft. (0.91 m) Blue Cat6 Right Angle to Straight RJ45 - RJ45 Patch cable

Features

- 3-ft. (0.91 m) Blue Cat6, Right Angle to Straight RJ45 RJ45 Patch cable
- PVC 4 Pair Stranded Conductors, 24AWG
- Fully Molded Ends
- ETL Verified to TIA/EIA -568-B
- 550Mhz Gigabit Speed Rated

Specifications

| OVERVIEW | | |
|----------------------|---------------------------------|--|
| UPC Code | 037332167521 | |
| Technology | Cat6 | |
| | | |
| CONNECTIONS | | |
| Side A - Connector 1 | RJ45 (MALE) | |
| Side B - Connector 1 | RJ45 (MALE) - RIGHT ANGLE | |
| Crossover Wiring | No | |
| Contact Plating | Gold | |
| PoE Type | Type 2 PoE+ (30W, IEEE 802.3at) | |
| Connector Type | Molded | |
| Wiring Configuration | EIA/TIA 568B | |
| Angled Connector | Yes | |





| PHYSICAL | | |
|---------------------------------|------------------------------|--|
| Cable Jacket Color | Blue | |
| Cable Jacket Material | PVC | |
| Cable Jacket Rating | СМ | |
| Cable Shielding | UTP | |
| Cable Outer Diameter (OD) | 6.0 mm | |
| Number of Conductors | 4 Pair | |
| Conductor Material | Stranded Copper | |
| Conductor Gauge | 24 AWG | |
| Cable Length (ft.) | 3 | |
| Cable Length (m) | 0.91 | |
| Cable Length (in.) | 36 | |
| Cable Length (cm) | 91.4 | |
| Shipping Dimensions (hwd / in.) | 0.25 x 6.50 x 8.00 | |
| Shipping Dimensions (hwd / cm) | 0.64 x 16.51 x 20.32 | |
| Shipping Weight (lbs.) | 0.10 | |
| Shipping Weight (kg) | 0.05 | |
| Unit Dimensions (hwd / in.) | 0.000 x 0.000 x 0.000 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | 14° to 122°F (-10° to 50°C) | |
| Storage Temperature Range | 5° to 140°F (-15° to 60°C) | |
| Operating Humidity Range | 0% to 90% RH, Non-Condensing | |
| Storage Humidity Range | 0% to 90% RH, Non-Condensing | |
| COMMUNICATIONS | | |
| Bandwidth per TIA Standard | 250 MHz | |
| Maximum Bandwidth as Tested | 500 MHz | |
| Network Compatibility | 1 Gbps (Gigabit) | |
| IEEE Standards Supported | 802.3an; 802.3at | |
| FEATURES & SPECIFICATIONS | | |
| Antibacterial | No | |
| IP68 Rated | No | |
| Snagless Connector | No | |
| STANDARDS & COMPLIANCE | | |





| Product Certifications | UL Listed; cUL Listed | |
|--|---|--|
| Product Compliance | CE (Europe); RoHS; IEEE 802.3an 10GBase-T; IEEE 802.3at PoE+; REACH; UKCA | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.