

SCSI/Fibre Channel - 4-ft. SCSI Cable HD68M to DB25M Double Shielded

MODEL NUMBER: \$402-004



Highlights

- Premium double-shielded cable
- 34 twisted-pair conductors

System Requirements

 Any external SCSI III device or controller card requiring HD68 or DB25 interface

Package Includes

 4-ft SCSI cable HD68M to DB25M double shielded

Description

Multi-platform SCSI III external peripheral cable HD68m to DB25M. This 4ft cable is designed to connect two SCSI III (fast SCSI) devices together. Manufactured using double shielded 25 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 25 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW		
UPC Code	037332014108	
CONNECTIONS		
Side A - Connector 1	HD68 (MALE)	
Side B - Connector 1	DB25 (MALE)	
PHYSICAL		
Cable Length (ft.)	4	



Cable Length (m)	1.22
Shipping Dimensions (hwd / in.)	11.75 x 7.00 x 0.75
Shipping Dimensions (hwd / cm)	29.84 x 17.78 x 1.90
Shipping Weight (lbs.)	0.54
Shipping Weight (kg)	0.24
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.