



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SNMPWEBCARD

For remote monitoring and control via SNMP, Web, or Telnet.

Highlights



- NEW firmware version 12.04.0055 now available! - supports SNMPv3
- Internal SNMP/Web management accessory card
- Simple installation and setup
- Data Logging
- Event Logging
- Flash Upgradeable
- Scheduling
- Email Notification
- NOTE: Existing 12.04.0048, 12.04.0049, 12.04.0051 and 12.04.0052 cards can be upgraded to the new firmware to provide SNMPv3 support

Description

Tripp Lite's SNMPWEBCARD allows network users to operate any expansion slot-equipped Tripp Lite SmartPro or SmartOnline UPS as a managed device on the network. Enables remote monitoring and control of UPS and site electrical conditions using the SNMP network management platform or a web browser. Provides remote viewing of site electrical data, UPS status information and self-test logs. Supports selective rebooting of locked network equipment without disrupting power to other devices when used with customized load management receptacles available on select Tripp Lite UPS systems. Optional ENVIROSENSE module provides remote temperature/humidity monitoring and a dry contact interface to control and monitor alarm, security and telecom devices. NEW firmware version 12.04.0055 now available! - supports SNMPv3. Firmware is not applicable with cards running firmware version 12.04.0047 or earlier. NOTE: Existing 12.04.0048, 12.04.0049, 12.04.0051 and 12.04.0052 cards can be upgraded to the new firmware to provide SNMPv3 support

Applications

- Ideal for remote management and control of UPS and power data in LAN/WAN racks, computer rooms and datacenter environments

Package Includes

- SNMPWEBCARD
- Quick Start Installation Guide
- Configuration Cable
- Software CD including Owner's Manual & MIB files
- Cover Plates (secures card in UPS system's SNMP accessory slot)

Features

- NEW firmware version 12.04.0055 now available! - supports SNMPv3 - NOTE: Existing 12.04.0048, 12.04.0049, 12.04.0051 and 12.04.0052 cards can be upgraded to the new firmware to provide SNMPv3 support
- Makes any slot-equipped Tripp Lite UPS a managed device on the network, controllable using SNMP network management platforms or a web browser
- Web interface provides remote viewing of current site electrical data, UPS self-test and alert logs, as well as logged power events such as blackouts, brownouts, overvoltages, and other electrical problems
- Offers the ability to control UPS output power and remote reboot of locked network devices without interrupting power to other loads when used with any Tripp Lite UPS equipped with load management receptacles
- DHCP/Manual configuration support provides the ability to have network settings automatically assigned to the card, or manually assigned via permanent IP addresses
- 10/100 Mbps auto-sensing allows optimal communication compatibility with your current 10/100 Base-T network
- Real-time clock support maintains the time of day and date even if the UPS is shut down
- NTP (Network Time Protocol) support gives the card the ability to receive automatic updates to its real-time clock from a NTP server

- 2-tier level access allows an administrator and a guest to log into the web browser for monitoring and/or management of slot-equipped Tripp Lite UPS systems
- Multiple user support allows for viewing by a number of users at the same time
- Full Telnet access gives you the ability to remotely monitor and manage your UPS system via a TELNET session
- Optional SSL (Secure Socket Layer) security setting provides the capability to create an encrypted connection to the card via a web browser
- Offers the ability to shut down remote operating systems through your networks. (Supported operating systems must have Power Alert 12 installed. See [PowerAlert section](#) for software support)
- Alert notifications via email or SNMP traps give users the added advantage of having an immediate event notification sent to them as a result of a site electrical or UPS problem.
- Protocols supported include HTTP, HTTPS, PowerAlert Network Management System, SMTP, SNMPv1, SNMPv2, Telnet, SSH, FTP, DHCP, BOOTP
- RoHS Compliant
- 2-year product warranty

Specifications

OVERVIEW	
Model Type	Hardware
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Environmental Monitoring	ENVIROSENSE	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	1
Extended Warranties	WEXT3-SNMP	3-Year Extended Warranty - For All SNMP Products	1
Extended Warranties	WEXT5-SNMP	5-Year Extended Warranty - For All SNMP Products	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3968.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.