



## 24-Outlet Power Strip with Industrial Surge Protector, 15 ft. (4.57 m) Cord, 1650 Joules, 72 in. length

## MODEL NUMBER: SS7619-15











### Description

The SS7619-15 6-ft. (1.83 m) power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center spacing, 15-ft. (4.57 m) AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 1650 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray color scheme.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 24 NEMA 5-15R ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle) FORMAT: 6-ft. (1.83 m) corded vertical/raceway power distribution strip SURGE SUPPRESSION: 1650 joules

### **Features**

- Long 6-ft./72-in. strip offers convenient power distribution and surge suppression in equipment racks, computer rooms, workbenches, raceways and more
- Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff with integrated 15 amp circuit breaker
- Adjustable mounting clips support installation in a variety of applications
- UL1363/1449 400V (USA), cUL (Canada)
- 15A power handling capacity with circuit breaker
- 1650-joule AC surge suppression
- 15-ft. (4.57 m) AC line cord

# **Specifications**

#### OVERVIEW

## Highlights

- 24 outlets
- 15-ft. (4.57 m) cord
- 72-in. length
- 1650-joule rating

## Package Includes

- SS7619-15 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual





	037332100283	
UPC Code	037332100203	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	22000	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	15	
Right-Angle Plug	No	
Input Cord Length (m)	4.57	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(24) 5-15R	
Circuit Breaker (amps)	15	
Right-Angle Outlets	No	
Outlet Spacing	2.795-in. (center to center)	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	No	
Switches	Combination AC circuit breaker and lighted two-position power switch controls power to all outlets	
Locking Switch Cover	Transparent locking switch cover prevents accidental shutoff	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1650	
UL1449 Let Through Rating	400V UL Verified	
Automatic Shut-Off	No	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	





PHYSICAL		
Material of Construction	Metal	
Power Cord Color	Black	
Housing Color	Silver	
Included Mounting Accessories	Set of adjustable mounting clamps	
Mounting Holes or Slots	No	
Outlets Measurement (Center to Center)	69mm	
Receptacle Color	Black	
Shipping Dimensions (hwd / in.)	2.40 x 3.20 x 75.50	
Shipping Dimensions (hwd / cm)	6.10 x 8.13 x 191.77	
Shipping Weight (lbs.)	5.60	
Shipping Weight (kg)	2.54	
Unit Dimensions (hwd / in.)	1.250 x 1.620 x 72.000	
Unit Dimensions (hwd / cm)	182.9 x 3.8 x 3.8	
Unit Weight (lbs.)	3.96	
Unit Weight (kg)	1.80	
Outlet Spacing	2.795-in. center-to-center spacing	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1449; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.