



Power It! 4-Outlet Power Strip, 6 ft. (1.83 m) Cord

MODEL NUMBER: TLM406NC



Highlights

- 4 outlets
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 6-ft. (1.83 m) power cord
- Rugged metal case
- Keyhole mounting slots

Package Includes

- TLM406NC power strip
- · Warranty information
- · Instruction manual

Description

The Power It!® TLM406NC power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes four NEMA 5-15R outlets, sixfoot (1.8 meters) AC power cord and keyhole mounting slots. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads.

Features

- Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment
- Includes 4 NEMA 5-15R outlets
- Illuminated on/off switch provides one-touch power control for connected equipment
- Transparent switch cover snaps tight to prevent accidental shutoff
- Convenient keyhole slots provide secure mounting options for a wide variety of surfaces and applications
- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 6-ft. (1.83 m) AC power cord
- Rugged metal case provides extra safety and durability
- UL certification

Specifications

OVERVIEW		
UPC Code	037332134370	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	





Recommended Electrical Service 15.120V Input Cord Gauge Type 14 gauge: SJT Voltage Compatibility (VAC) 120 Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (ft.) 1.83 Insignated Cord Clip No OUTPUT Frequency Compatibility 50 / 80 Hz Output Receptacles (4) 5-15R Crout Breaker (amps) 15 Overload Protection 15 A Circuit breaker Transformer Accommodation 15 A Circuit breaker Outlet Orientation Single row of 4 Right-Angle Outlets No Switches Users INTERFACE, ALERTS & O'T'C' 1 Suffice of your of 4 Right-Angle Outlets 1 Spife or your of 4 Right-Angle Outlets 1 Spife or your of 4 Switches 1 Spife or your of your of your of your your your your your your your your				
Votage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (R.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No COUTHING Frequency Compatibility 50 / 60 Hz Cutul Receptacles (4) 5-15R Cutual Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Right-Angle Outlets No Sex INTERFACE, ALERTS & CONTRACT Switch Cover Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Metal Group Light Gray Material of Construction Metal Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm	Recommended Electrical Service	15A 120V		
Input Piug Type NEMA 6-16P Input Card Length (It.) 6 Right-Angle Plug No Input Card Length (m) 1.83 Interest Cord Clip No OUTPUT OUTPUT COUTPUT Frequency Compatibility 50 / 60 Hz Output Recaptacles (4) 5-15R Clorual Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & COVENA Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Housing Color Light Gray Mounting Poles or Slots Yes Slot or Hole Mount Measurement (Center to Center) Light gray Slot or Hole Mount Measurement	Input Cord Gauge Type	14 gauge; SJT		
Input Cord Length (tt) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integral Cord Clip No OUTPUT Description of The Control of	Voltage Compatibility (VAC)	120		
Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (4) 6-15R Circuit Breaker (amps) 15A circuit breaker Circuit Breaker (amps) 15A circuit breaker Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Housing Color Light Gray Mounting Holes or Siots Yes Slor or Note Mount Measurement Color to Lock Mount Measurement Centers to Control Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Curlets Measurement Centers to Control Light gray Shipping Dimensions (hwd / cm) 45.20 x 10.20 x 5.6	Input Plug Type	NEMA 5-15P		
Input Card Length (m) 1.83 Integrated Card Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Overload Protection 15x circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Joba Mount Measurement (Center to Coloria) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Coloria) Light gray Shipping Dimensions (hwd / cm) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 84.01 x 25.81 x 14.22 Shipping	Input Cord Length (ft.)	6		
Integrated Cord Clip No OUTPUT Frequency Compatibility Frequency Congrated Cord Frequency Congrated Congrated Cord Frequency Congrated Con	Right-Angle Plug	No		
Frequency Compatibility 50 / 60 Hz Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & COTTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Mounting Holes or Slots Yes Stor of Hole Mount Measurement (Center to Center) Cutlets Measurement (Center to Center) Shipping Dimensions (hwd / m) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (kg) 0.77	Input Cord Length (m)	1.83		
Frequency Compatibility 50 / 60 Hz Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps light to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.80 Shipping Dimensions (hwd / on) 64.01 x 25.91 x 14.22 Shipping Weight (bs.) 1.70 Shipping Weight (kg) 0.77	Integrated Cord Clip	No		
Output Receptacles (4) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & COVENOUS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Metair of Construction Metal Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	ОИТРИТ			
Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Cutlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / m.) 5.20 x 10.20 x 5.60 Shipping Dimensions (hwd / m.) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg.) 0.77	Frequency Compatibility	50 / 60 Hz		
Overload Protection 15A circuit breaker Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Cutlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / om) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Output Receptacles	(4) 5-15R		
Transformer Accommodation (2) Yes Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Circuit Breaker (amps)	15		
Outlet Orientation Single row of 4 Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Overload Protection	15A circuit breaker		
Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Transformer Accommodation	(2) Yes		
Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Light gray Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (kg) 0.77	Outlet Orientation	Single row of 4		
Switches Lighted 2 position switch controls power to all outlets PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Right-Angle Outlets	No		
PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Shipping Dimensions (hwd / in.) Shipping Weight (lbs.) Shipping Weight (kg) Tansparent switch cover snaps tight to prevent accidental shutoff Tansparent switch cover snaps tight to prevent accidental shutoff Tansparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Light Gray Metal Attalled Attalled	USER INTERFACE, ALERTS & COM	USER INTERFACE, ALERTS & CONTROLS		
PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Qutlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Switches	Lighted 2 position switch controls power to all outlets		
ColorLight GrayMaterial of ConstructionMetalPower Cord ColorLight GrayHousing ColorLight GrayMounting Holes or SlotsYesSlot or Hole Mount Measurement (Center to Center)Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mmOutlets Measurement (Center to Center)1.18 in.Receptacle ColorLight grayShipping Dimensions (hwd / in.)25.20 x 10.20 x 5.60Shipping Dimensions (hwd / cm)64.01 x 25.91 x 14.22Shipping Weight (lbs.)1.70Shipping Weight (kg)0.77	Locking Switch Cover	Transparent switch cover snaps tight to prevent accidental shutoff		
Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Light gray Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Metal Metal Metal Metal Metal Metal Anal Metal Light Gray Alight Gray Distance between Meyhole tabs = 127mm; Distance between end tabs = 207.45mm Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Alight Gray Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Alight Gray Ali	PHYSICAL			
Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Outlets Measurement (Center to Center) Light gray Shipping Dimensions (hwd / in.) Shipping Weight (lbs.) Shipping Weight (kg) Light Gray Light Gray Light Gray Yes Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Light gray 1.18 in. 25.20 x 10.20 x 5.60 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70	Color	Light Gray		
Housing ColorLight GrayMounting Holes or SlotsYesSlot or Hole Mount Measurement (Center to Center)Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mmOutlets Measurement (Center to Center)1.18 in.Receptacle ColorLight grayShipping Dimensions (hwd / in.)25.20 x 10.20 x 5.60Shipping Dimensions (hwd / cm)64.01 x 25.91 x 14.22Shipping Weight (lbs.)1.70Shipping Weight (kg)0.77	Material of Construction	Metal		
Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) 1.18 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Power Cord Color	Light Gray		
Slot or Hole Mount Measurement (Center to Center) Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm Outlets Measurement (Center to Center) Light gray Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) Shipping Weight (kg) 0.77	Housing Color	Light Gray		
Outlets Measurement (Center to Center) Light gray Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Distance between keynole tabs = 12/min, Distance between end tabs = 207.45min 1.18 in. 1.18 in. 25.20 x 10.20 x 5.60 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 0.77	Mounting Holes or Slots	Yes		
Receptacle Color Light gray Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) Shipping Weight (kg) 0.77	Slot or Hole Mount Measurement (Center to Center)	Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm		
Shipping Dimensions (hwd / in.) 25.20 x 10.20 x 5.60 Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Outlets Measurement (Center to Center)	1.18 in.		
Shipping Dimensions (hwd / cm) 64.01 x 25.91 x 14.22 Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Receptacle Color	Light gray		
Shipping Weight (lbs.) 1.70 Shipping Weight (kg) 0.77	Shipping Dimensions (hwd / in.)	25.20 x 10.20 x 5.60		
Shipping Weight (kg) 0.77	Shipping Dimensions (hwd / cm)	64.01 x 25.91 x 14.22		
	Shipping Weight (lbs.)	1.70		
Unit Dimensions (hwd / in.) 2.000 x 8.750 x 2.500	Shipping Weight (kg)	0.77		
	Unit Dimensions (hwd / in.)	2.000 x 8.750 x 2.500		





Unit Dimensions (hwd / cm)	22.2 x 6.4 x 5.1	
Unit Weight (lbs.)	1.4	
Unit Weight (kg)	0.64	
Mounting Details	Includes flanges	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	
Built-In Circuit Breaker	Yes	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks

are the property of their respective owners.