



USB over Cat5 Extender Kit

MODEL NUMBER: U007-40M





Highlights

- Locate a USB 1.1 peripheral up to 150 feet from your computer
- Uses readily available Cat5/Cat6 cable
- Bus-powered; no external power supply required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

- · Local transmitter unit
- · Remote receiver unit
- Owner's manual

Description

Tripp Lite's USB 1.1 over Cat5 Extender Kit allows you to connect your computer to a USB 1.1 peripheral up to 150 feet away using ordinary Cat5/Cat5e/Cat6 cable. The transmitter and receiver kit is buspowered, so no external power supply is required. Plug-and-play; no software or drivers needed. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Features

- Locate a USB 1.1 peripheral up to 150 feet from your computer
- Bus Powered no additional AC adapters required
- Uses readily available Cat5/Cat5e/Cat6 cable (not included)
- Transfer rates of 1.5Mbps to 12Mbps
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
UPC Code	037332138095	
CONNECTIONS		
Side A - Connector 1	USB A (MALE)	
Side A - Connector 2	RJ45 (FEMALE)	
Side B - Connector 1	USB A (FEMALE)	
Side B - Connector 2	RJ45 (FEMALE)	
PHYSICAL		





Color	Black	
Cable Length (ft.)	131	
Cable Length (m)	39.94	
Receiver Unit Height (in.)	0.9	
Receiver Unit Width (in.)	1.8	
Receiver Unit Depth (in.)	2.6	
Shipping Dimensions (hwd / in.)	1.50 x 5.40 x 7.80	
Shipping Dimensions (hwd / cm)	3.81 x 13.72 x 19.81	
Shipping Weight (lbs.)	0.50	
Shipping Weight (kg)	0.23	
Transmitter Unit Depth (in.)	2.6	
Transmitter Unit Height (in.)	0.9	
Transmitter Unit Width (in.)	1.8	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	1-year limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.