



Protect It! 2-Connector (C8, 2-Prong) In-Line Surge Protector, 306 Joules, Tel/Ethernet Protection

MODEL NUMBER: TRAVELERC8







Description

Tripp Lite's Traveler In-Line surge suppressor features a 306 joule rating to handle even the strongest surges. In-line design, over current protection and 120/240V compatibility make this surge suppressor ideal for notebook computers and PDAs. Integrated phone line protection allows you to safeguard tel/modem and AC connections with a single unit. "Protected" LED lets you instantly know whether your wall jacks have potentially damaging signals. \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

CONNECTORS: interfaces with C8 (2 conductor laptop type) cabling

ELECTRICAL: 120V and 240V AC, 50/60Hz

FORMAT: In-line design that puts surge protection between your notebook computer or PDAs' power adapter and the power cord leading to the wall outlet

SUPPRESSION: AC: 150V RMS Clamping/306 joules/900V UL1449 3rd Edition let-through rating

Features

- In-line design places AC line surge protection between your notebook computer or PDAs' power adapter and the power cord leading to the wall outlet
- 120/240V compatibility operates on voltage worldwide, automatically switching between 120V or 240V AC power
- Surge suppression rating: 306 joules
- Includes two 2-prong (C8) connectors
- Built-in LED confirms suppressor "protection present" (green)
- 1 line in/1 line out tel/modem/Ethernet combo
- Single small push-button switch activates overcurrent detection circuit
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected equipment
- Automatic shutoff cuts power to outlets when the protection circuit has been compromised

Highlights

- 120V/240V compatible
- 306 joule rating Two 2-prong (C8) connectors
- 1 in/1 out tel/modem/Ethernet combo in-line design
- Retractable Ethernet cable
- Diagnostic LED
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Package Includes

- TRAVELERC8 surge suppressor
- Instruction manual with warranty information





Specifications

OVERVIEW		
UPC Code	037332119100	
INPUT		
	120V AC; 230V AC	
Nominal Input Voltage(s) Supported Recommended Electrical Service		
	120V (110-125V), 230V (220-250V)	
Input Cord Length Details	In-line	
Voltage Compatibility (VAC)	120; 230	
Maximum Surge Amps	12000	
Input Plug Type	IEC-320-C8	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(2) C8 2-prong	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Single small push-button switch activates over-current detection circuit	
Diagnostic LED Details	Built-in LED confirms suppressor "protection present" (green)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	306	
AC Suppression Response Time	< 1 ns	
UL1449 Let Through Rating	900V - UL Verified	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection Details	1 line	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	Yes	





Telephone/DSL Protection	Yes
PHYSICAL	
Color	Black
Material of Construction	Plastic
Power Cord Color	Black
Form Factors Supported	In-line
Housing Color	Black
Mounting Holes or Slots	No
Receptacle Color	Black
Shipping Dimensions (hwd / in.)	8.66 x 5.93 x 1.83
Shipping Dimensions (hwd / cm)	22.00 x 15.06 x 4.65
Shipping Weight (lbs.)	0.37
Shipping Weight (kg)	0.17
Unit Dimensions (hwd / in.)	3.540 x 2.560 x 1.500
Unit Dimensions (hwd / cm)	8.99 x 6.5 x 3.81
Unit Weight (lbs.)	.3
Unit Weight (kg)	0.14
FEATURES & SPECIFICATIONS	
Rotatable Outlets	No
Antimicrobial	No
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$50,000 Ultimate Lifetime Insurance

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.