# **Owner's Manual**

# USB-C<sup>™</sup> Triple Display Docking Station

Model: U442-DOCK7D-B

USB Type-C and USB-C are trademarks of USB Implementers Forum

Este manual esta disponible en español en la página de Tripp Lite: tripplite.com/support

Ce manuel est disponible en français sur le site Web de Tripp Lite : tripplite.com/support

Русскоязычная версия настоящего руководства представлена на веб-сайте компании Tripp Lite по адресу: tripplite.com/support

#### **PROTECT YOUR INVESTMENT!**

Register your product for quicker service and ultimate peace of mind. You could also win an ISOBARGULTRA surge protector—a \$100 value!

tripplite.com/warranty





1111 W. 35th Street, Chicago, IL 60609 USA tripplite.com/support

Copyright © 2019 Tripp Lite. All rights reserved.

10-160 93-3B67.indd 1 10/31/2019 3:14:16 F

## **Product Features**

- All-in-one docking station includes ports for HDMI, DisplayPort, VGA, Gigabit Ethernet, USB-C (x2), USB-A (x5) and 100W Power Delivery (PD) charging.
- Connect up to three displays simultaneously and extend across all displays (up to three).
- Supports HDMI and DisplayPort video resolutions up to 4096 x 2160
  30 Hz.
- Supports VGA video resolutions up to 1920 x 1200 @ 60 Hz.
- Ethernet port supports true 10/100/1000 Mbps network speeds.
- PD 3.0 Fast Role Swap maintains data and power connections upon removal and connection of charging power adapter.
- USB-C PD charging port supports power input up to 20V/5A (100W).
- Supports dynamic current detection and power distribution enabling your source (host) to be charged at a dynamic power level instead of a fixed power level.
- Dedicated BC 1.2-compliant USB-A port provides up to 1.5A of fast charging power to mobile devices.
- Secure Digital v3.0 SD/Micro SD card slots for external memory may be used simultaneously.
- USB 3.0 and USB 2.0 ports support 5 Gbps and 480 Mbps data transfer speeds respectively.
- Thunderbolt 3 compatible.
- Plug-and-play design no software, drivers or external power required.


# **Package Contents**

- U442-DOCK7D-B
- USB 3.1 Type-C Cable 1 ft. (0.3 m), Black
- · Owner's Manual

# **Optional Accessories**

- N201-Series Cat6 Gigabit Snagless Patch Cables
- P312-Series 3.5 mm Mini Stereo Audio Cables
- P502-Series High-Resolution VGA Cables
- P569-Series High-Speed HDMI Cables
- P580-Series DisplayPort Cables with Latches
- U322-Series USB 3.0 A/B Device Cables
- U420-Series USB 3.1 Gen 1 C/C Cables
- U428-Series USB 3.1 Gen 1 A/C Cables
- M100-Series USB Sync/Charge Cable USB-A to Lightning

# **Product Overview**



## **Product Overview**

- USB Type-C To Host: Connect this port to the host (source) via the removable USB-C to USB-C cable.
- 2 USB Type-C Cable: Detachable USB-C to USB-C cable connects the host to the docking station.
- Anti-Theft Lock: Connect a user-supplied computer/laptop security cable lock.
- USB Type-C PD Charging Port: Connect a device's PD Power Adapter here.
- 6 HDMI Port: Connect an HDMI monitor.
- **6 DisplayPort Port:** Connect a DisplayPort monitor.
- VGA Port: Connect a VGA monitor.
- 8 RJ45 Port: Connect to a 10/100/1000 Mbps network.
- SD/Micro SD Card Slot: Insert SD and Micro SD memory cards.
- USB-A 2.0 Ports (x2): Connect up to two USB 2.0 peripherals or devices.
- USB-A 3.0 Ports (x2): Connect up to two USB 3.0 peripherals or devices.
- USB-A 3.0 with BC 1.2 Port: Supports 5V 1.5A charging for power-hungry devices.
- USB Type-C Data Only Port: Supports the transmission of data up to 5 Gbps.
- **3.5 mm Mini Stereo Port:** Connect speaker or microphone.
- Power Button: Turns the unit off and on.
- LED: Green LED illuminates when the unit is on and receiving power.

## Installation

#### Notes:

- Maximum resolutions when all three displays are connected are 1920 x 1080 @ 60 Hz in SST (Single Stream Transport) mode and 1280 x 720 @ 60 Hz in MST (Multi Stream Transport) mode.
- Mac OS laptops or computers will only extend to one monitor. The others will be mirrored.
- Detach the USB 3.1 Type-C cable from the unit. Plug the right-angled USB-C connector to the docking station and the straight USB-C connector to your source (e.g. laptop).
- Connect up to three monitor(s) using the available HDMI, VGA and DisplayPort video ports.

**Note:** Up to three monitor screens can be extended, providing a total of four separate screens (including your source's screen). The following table defines the maximum video resolutions based on specific configurations while in SST and MST modes.

SST Mode (Single Downstream Display)				
Ports	VGA	HDMI	DP	
Single Display	1080p/60 Hz	N/A	N/A	
Connected	N/A	4K/30 Hz	N/A	
	N/A	N/A	4K/30 Hz	
Dual Displays	1080p/60 Hz	1080p/60 Hz	N/A	
Connected	1080p/60 Hz	N/A	1080p/60 Hz	
	N/A	4K/30 Hz	4K/30 Hz	
Triple Displays Connected	1080p/60 Hz	1080p/60 Hz	1080p/60 Hz	

## Installation

MST Mode (Multiple Downstream Displays)				
Ports	VGA	HDMI	DP	
Single Display	1080p/60 Hz	N/A	N/A	
Connected	N/A	4K/30 Hz	N/A	
	N/A	N/A	4K/30 Hz	
Dual Displays	1080p/60 Hz	1080p/60 Hz	N/A	
Connected	1080p/60 Hz	N/A	1080p/60 Hz	
	N/A	4K/30 Hz	4K/30 Hz	
Triple Displays	720p/60 Hz	720p/60 Hz	720p/60 Hz	
Connected				

- 3. Connect up to two USB 2.0 peripherals such as a keyboard and mouse.
- 4. Connect up to three USB 3.0 peripherals.

**Note:** The USB 3.0 BC 1.2-compliant port supports up to 7.5W (5V 1.5A) of charging power.

- Connect to an Ethernet network through the RJ45 port to achieve speeds up to 10/100/1000 Mbps.
- Connect the 3.5 mm Mini Stereo port to a microphone or speaker with a user-supplied 3.5 mm audio cable.
- Insert an SD or Micro SD card into the corresponding memory card slots to access external memory.

**Note:** Both memory card slots may be used simultaneously.

- 8. Transfer data at speeds up to 5 Gbps using the USB Type-C data port.
- Charge the source device by connecting its USB-C PD Charger to the docking station's USB-C PD Charging port for up to 100W (20V 5A) of charging power.
- 10. Connect a security cable lock to the anti-theft lock port (optional).

# **Specifications**

Input Connector	
USB-C	USB Type-C, Female
Output Connector(s)	
USB-A	USB 3.0, Female (x3), USB 2.0, Female (x2)
USB-C	USB-C Data Only, Female
	USB-C PD Charge Only, Female
Ethernet	RJ45, Female
VGA	VGA, Female
HDMI	HDMI, Female
DisplayPort	DisplayPort, Female
Audio	3.5 mm, Female
Memory Cards	SD, Micro SD
Environmental	
Operating Temperature	32° to 113°F (0 to 45°C)
Operating Humidity	10% to 85% RH, Non-Condensing
Storage Temperature	14° to 158°F (-10 to 70°C)
Storage Humidity	5% to 90% RH, Non-Condensing
Mechanical	
Unit Dimensions	0.71 x 13.76 x 2.91 in. (18.1 x 348 x 74 mm)
[H x W x D]	
Unit Weight	0.55 lb. (0.25 kg)

# Specifications

Specifications	
HDMI Specification	1.4
HDCP Specification	1.4
DisplayPort	1.2
Specification	
Maximum Supported	HDMI (4096 x 2160 @ 30 Hz),
Video Resolution(s)	DisplayPort (4096 x 2160 @ 30 Hz),
	VGA (1920 x 1200 @ 60 Hz)
Network Speed	10/100/1000 Mbps or 1 Gbps
Color Depth (HDMI)	36 bit (12 bits per channel)
Chroma Subsampling	YCbCr: 4:4:4, 4:2:2, 4:2:0 and RGB: 4:4:4
(HDMI)	
Audio Specifications	LPCM 7.1 Channel Surround Sound Audio
PD Charging	PD 3.0 (100W)
Specification	

## **Warranty and Product Registration**

#### 3-Year Limited Warranty

TRIPP LITE warrants its products to be free from defects in materials and workmanship for a period of three (3) years from the date of initial purchase. TRIPP LITE's obligation under this warranty is limited to repairing or replacing (at its sole option) any such defective products. To obtain service under this warranty, you must obtain a Returned Material Authorization (RMA) number from TRIPP LITE or an authorized TRIPP LITE service center. Products must be returned to TRIPP LITE or an authorized TRIPP LITE service center with transportation charges prepaid and must be accompanied by a brief description of the problem encountered and proof of date and place of purchase. This warranty does not apply to equipment, which has been damaged by accident, negligence or misapplication or has been altered or modified in any way.

EXCEPT AS PROVIDED HEREIN, TRIPP LITE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCI UDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Some states do not permit limitation or exclusion of implied warranties; therefore, the aforesaid limitation(s) or exclusion(s) may not apply to the purchaser.

EXCEPT AS PROVIDED ABOVE, IN NO EVENT WILL TRIPP LITE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS PRODUCT, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. Specifically, TRIPP LITE is not liable for any costs, such as lost profits or revenue, loss of equipment, loss of use of equipment, loss of software, loss of data, costs of substitutes, claims by third parties, or otherwise.

#### PRODUCT REGISTRATION

Visit tripplite.com/warranty today to register your new Tripp Lite product. You'll be automatically entered into a drawing for a chance to win a FREE Tripp Lite product!\*

\* No purchase necessary. Void where prohibited. Some restrictions apply. See website for details.

#### WEEE Compliance Information for Tripp Lite Customers and Recyclers (European Union)



Under the Waste Electrical and Electronic Equipment (WEEE) Directive and implementing regulations, when customers buy new electrical and electronic equipment from Tripp Lite they are entitled to:

- Send old equipment for recycling on a one-for-one, like-for-like basis (this varies depending on the country)
- Send the new equipment back for recycling when this ultimately becomes waste

#### WARNING

Use of this equipment in life support applications where failure of this equipment can reasonably be expected to cause the failure of the life support equipment or to significantly affect its safety or effectiveness is not recommended.

Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos and illustrations may differ slightly from actual products.

10





1111 W. 35th Street, Chicago, IL 60609 USA • tripplite.com/support

19-10-160 93-3B67\_RevA

10-160 93-3B67.indd 12 10/31/2019 3:14:16 F